

± 120 -
150mm

Image shown above 73.20 with round canopy

± 230 - 380mm

| | |
|-----------------|--|
| Series | 73 |
| Mounting | Ceiling mounted |
| Glass Colours | Clear, grey 1, grey 2, grey 3 |
| Lamp | 1W LED, 2700K, 100lm (2500K and 3000K options available) 10W Xenon, 2600K, 81lm |
| Coaxial Length | 3000mm standard / up to 30500mm maximum Adjustable length: 73.1 - 73.3 Non-adjustable length: 73.8 - 73.20 |
| Canopy Finishes | 73.1 - 73.3: white, black or brushed nickel canopy 73.1m: white, black, brushed nickel, or brushed brass canopy 73.8 - 73.20: white canopy |
| Materials | Blown glass, braided metal coaxial cable, electrical components, steel canopy |
| Power Supply | Integral Remote mounted for 73.1m Bocci recommends remote mounting power supplies for ease of long-term maintenance. |
| Environment | Indoor, dry location. IP30 |
| Note | Every single Bocci product is handmade. Each one is variously blown, poured, carved, polished, packed and dispatched directly by us. As such, no two products are identical; they are individual, irregular expressions of our research. |
| Patent # | US D762,323 S EU 002633230-0001 - 0003 |

Certifications



Weight (kg)



Round

| | |
|-------|-----|
| 73.1 | 2.7 |
| 73.3 | 8 |
| 73.8 | 33 |
| 73.11 | 43 |
| 73.20 | 69 |



Rectangle


| | |
|-------|----|
| 73.8 | 32 |
| 73.11 | 40 |
| 73.20 | 68 |




Square

| | |
|-------|----|
| 73.20 | 75 |
|-------|----|

ADJUSTABLE LENGTH



NON-ADJUSTABLE LENGTH



Best practices for wiring multiple single pendant fixtures with remote mounted power supplies:

- Multiple single pendant fixtures should be wired in parallel. DO NOT wire in series.
- Bocci recommends a home run line for each fixture location to avoid significant voltage drop.
- Calculations for distance to the power supply, or required wire gauge in order to avoid voltage drop, are the responsibility of the installing party.

All dimensions are in millimeters (mm) unless otherwise specified.