

Image shown above 100.19 with round canopy

| Series | 100 |
|------------------|---|
| Mounting | Ceiling mounted |
| Glass Colours | Clear, grey, pink |
| Lamp | 1W LED, 2700K, 100Im (2500K and 3000K options available) |
| Sculptural Cable | 3000mm standard ∕ up to 30500mm maximum Adjustable length: 100.1 - 100.7 Non-adjustable Length: 100.13 - 100.61 |
| Cable Finishes | Black or nickel |
| Anchor Finishes | White, black, brass, brushed nickel |
| Canopy Finishes | 100.1 - 100.7: white, black or brushed nickel canopy 100.1m: white, black, brushed nickel, or brushed brass canopy 100.13 - 100.61: white canopy |
| Material | Blown glass, braided metal cable, electrical components, steel canopy |
| Power Supply | Integral Remote mounted for 100.1m |
| | Bocci recommends remote mounting power supplies for ease of long-term maintenance. |
| Environment | Indoor, dry location. IP30 |
| Note | Pendant anchor kit included. |
| | Every single Bocci product is handmade. Each one is variously blown, poured, carved, polished, packed and dispatched directly by us. As such, no two products are identical; they are individual, irregular expressions of our research. |
| Patent # | US D1027 281S EU 008526131-0001 |
| Certifications | |

O P

± 210 - 170mm

| Round | |
|--------|-------|
| 100.1 | 3.5 |
| 100.3 | 10.8 |
| 100.7 | 24.4 |
| 100.13 | 50.1 |
| 100.19 | 76.6 |
| 100.37 | 126.5 |
| 100.61 | 220.5 |

Weight (kg)

Best practices for wiring multiple single pendant fixtures with remote mounted power supplies:

- Multiple single pendant fixtures should be wired in parallel, DO NOT wire in series.
- Bocci recommends a home run line for each fixture location to avoid significant voltage drop.
- Calculations for distance to the power supply, or required wire gauge in order to avoid voltage drop, are the responsibility of the installing party.

ADJUSTABLE LENGTH



NON-ADJUSTABLE LENGTH



Ø707

All dimensions are in millimeters (mm) unless otherwise specified.