

Image shown above 38.7V with round canopy

Ø190 - 215mm

Series	38V
Mounting	Ceiling mounted
Glass Colour	Clear
Lamp	1W LED, 2700K, 100lm 10W Xenon, 2600K, 81lm
Sculptural Cable	3000mm standard / up to 30500mm maximum Adjustable length: 38.1V - 38.7V Non-adjustable Length: 38.13V - 38.61V
Cable Finishes	Black or nickel
Canopy Finishes	38.1V - 38.7V: white, black or brushed nickel canopy 38.1Vmi/mo: white polyurethane canopy 38.13V - 38.61V: white canopy
Materials	Blown glass, braided metal cable, electrical components, steel canopy
Power Supply	Integral Remote mounted for 38.1Vmi/mo/mi  Bocci recommends remote mounting power supplies for ease of long-term maintenance.
Environment	Indoor, dry location. IP30
Note	Pendant anchor kit included.  Every single Bocci product is handmade. Each one is variously blown, poured, carved, polished, packed and dispatched directly by us. As such, no two products are identical; they are individual, irregular expressions of our research.

Patent # US 002071019-001

Certifications



CB

CE

UK

CA



Weight (kg)




Round


38.1V	2.7
38.3V	8.2
38.7V	18
38.13V	32.7
38.19V	54.5
38.37V	104.6
38.61V	166.6

- Best practices for wiring multiple single pendant fixtures with remote mounted power supplies:**
- Multiple single pendant fixtures should be wired in parallel, DO NOT wire in series.
  - Bocci recommends a home run line for each fixture location to avoid significant voltage drop.
  - Calculations for distance to the power supply, or required wire gauge in order to avoid voltage drop, are the responsibility of the installing party.

## ADJUSTABLE LENGTH



## NON-ADJUSTABLE LENGTH



All dimensions are in millimeters (mm)  
unless otherwise specified.