

± 150mm

Image shown above 76.11 with rectangular canopy

Series	76
Mounting	Ceiling mounted
Glass Colour	Clear, grey, green
Lamp	0.4W LED, 2700K, 70lm
Coaxial Length	3000mm standard / up to 30500mm maximum Adjustable length: 76.1 - 76.7 Non-adjustable Length: 76.11 - 76.36
Canopy Finishes	76.1 - 76.7: white, black or brushed nickel canopy 76.11 - 76.36: white canopy
Materials	Blown glass, copper mesh, braided metal coaxial cable, electrical components, steel canopy
Power Supply	Integral Remote mounted for 76.1m Bocci recommends remote mounting power supplies for ease of long-term maintenance.
Environment	Indoor, dry location. IP30
Note	Every single Bocci product is handmade. Each one is variously blown, poured, carved, polished, packed and dispatched directly by us. As such, no two products are identical; they are individual, irregular expressions of our research.
Patent #	US D817,524 S EU 002840975-0004-0007

Weight (kg)



Round

76.1	0.7
76.3	2
76.5	3.4
76.7	7.2
76.14	20.9
76.26	30.4
76.36	39.5



Square

76.11	18.9
76.26	32.7
76.36	44.1




Rectangle


76.11	18
76.14	20
76.20	27.3
76.26	28.2
76.36	40

Certifications

ADJUSTABLE LENGTH



NON-ADJUSTABLE LENGTH





All dimensions are in millimeters (mm) unless otherwise specified.



Best practices for wiring multiple single pendant fixtures with remote mounted power supplies:

- Multiple single pendant fixtures should be wired in parallel. DO NOT wire in series.
- Bocci recommends a home run line for each fixture location to avoid significant voltage drop.
- Calculations for distance to the power supply, or required wire guage in order to avoid voltage drop, are the responsibility of the installing party.



NON-ADJUSTABLE LENGTH





1000 x 335



600



1100 x 370



755

up to 3000
standard

up to 30500
custom

All dimensions are in millimeters (mm) unless otherwise specified.